

UPS5000-A Series

(30-120kVA)

Introduction

The UPS5000-A (30-120kVA) is an online, double-conversion, and tower/rack convertible UPS that Huawei has launched. It uses the digital signal processing (DSP) technology to output pure and stable sine wave with a voltage of 380/400/415 Vac. With comprehensive reliability assurance measures and other leading technologies, the UPS5000-A (30-120kVA) can provide reliable, economical, intelligent, and convenient solutions to medium power scenarios.

Scenarios

- Small- and medium-sized data centers
- Telecom and Internet switch rooms
- Equipment rooms of branch offices in sectors such as finance
- Infrastructures, such as control equipment rooms, wireless systems, etc.

Features

Reliable

- Wide input voltage range to minimize battery use: 485-305 Vac for 100% load; 305-138 Vac for 100%-40% load (derating linearly)
- High output power factor of up to 1, 30% more load driven than traditional UPS

Efficient

- High efficiency at online mode of up to 95.7%, reducing power consumption of UPS and cooling equipment effectively

Simple

- Rack/tower convertible, suitable for different installation scenarios
- Flexible battery configuration: 30-40 batteries per string allow customers to get the faulty battery out instead of replacing it



UPS5000-A-30/40K



UPS5000-A-60/80/120K

Specifications

Rated Capacity (kVA/kW)		30kVA/30kW	40kVA/40kW	60kVA/60kW	80kVA/80kW	120kVA/120kW
Mains Input	Input Wiring	3Ph+N+PE				
	Rated Voltage	380/400/415 Vac				
	Voltage Range	138-485 Vac				
	Frequency Range	40-70 Hz				
	Total Harmonic Distortion	THDi<3% for 100% linear load				
	Input Power Factor	0.99				
Bypass Input	Input Wiring	3Ph+N+PE				
	Rated Voltage	380/400/415 Vac				
	Input Frequency	50/60±6 Hz				
Battery	Rated Voltage	360-480 Vdc (The number of batteries can be selected from 30 to 40; 32 batteries in default)				
Output	Output Wiring	3Ph+N+PE				
	Rated Voltage	380/400/415 Vac±1%				
	Frequency	Tracking the bypass input (Online mode); 50/60 Hz±0.1% (Battery mode)				
	Waveform	Sine wave (THDv<1% for 100% linear load)				
	Overload Capacity	110% overload for 60 minutes; 125% overload for 10 minutes; 150% overload for 1 minute				
System	Output Power Factor	1				
	Efficiency	Up to 95.7%				
	Expandability	Up to 4 units connected in parallel				
Environment	Operating Temperature	0-40°C				
	Storage Temperature	-40-70°C				
	Relative Humidity	0%-95% (No condensing)				
	Operating Altitude	1000 m. Above 1000 m, derating according to IEC62040-3				
	Audible Noise	≤58 dB		≤64 dB		
Others	Height×Width×Depth	500 mm × 264 mm × 800 mm		1020 mm × 440 mm × 850 mm		
	Weight	70 kg		200 kg		240 kg
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB; RoHS, REACH, WEEE, etc.				
	Communications	Dry contacts, RS485, SNMP				

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-022333-20150423-C-3.0
www.huawei.com